Crimping

EK 60/22 Battery powered hydraulic crimping tool 6 - 300 mm²











- **⇔**Large crimping range up to 300 mm²
- ⇐ Fast crimp cycles due to Automatic Retraction Stop (ARS)
- ⇔All tool data in view thanks to display and i-press app

Characteristics

- Choose your battery system: Bosch or Makita
- All data can be easily read via Bluetooth
- Closed head, flip top style, rotatable
- Quality assurance via visual and audible signals in case of error
- Simple and safe: One-button operating concept for controlling all tool functions
- Effortless working due to balanced centre of gravity
- LED for work area illumination
- Simple and safe: Automatic retraction when operation is complete
- Automatic retract stop (ARS) for positioning control in case of multiple crimps
- Always ready-to-use thanks to battery charge and service display

Suitable for

22-series interchangeable dies, narrow crimping

Technical data					
Crimping force	60 kN				
Hub	17 mm				
Crimping range	6 - 300 mm ²				
Crimping cycle	3 s to 5 s (depending on crimp cross-section)				
Charging time	45 min.				
Weight incl. battery	4.4 kg				
Ambient temperature	-10 °C up to +40°C				
Item		Part NoBos	sch	Part NoMakita	
Battery powered hydraulic crimping tool 6 - 300 m		mĚK6022C	FB	EK6022CFM	
Scope of supply					Page
Bosch battery 18 V / 5.0 Ah, Li-Ion		RALB2E	U		485
Bosch quick-charger for 18 V Li-Ion battery		LGLB1E	U		486
Makita battery 18 V / 4.0 Ah,	Li-lon			RAL40	484
Makita quick-charger for 18	V Li-Ion battery			LGL1	486
Plastic case		KK120N	G	KK120NG	
Accessories					Page
Bosch battery 18 V / 5.0 Ah,	Li-lon	RALB2E	U		485
Makita battery 18 V / 4.0 Ah,	Li-lon			RAL40	484
Item				Part No.	Page
EK 60/22 with crimping die set D 22 from 16 - 240 mm ² EK6022CFMSETD					
EK 60/22 with crimping die set R 22 from 16 - 240 mm ² EK6022CFMSETR					